

PATENT COOPERATION TREATY

PCT

17
26 MAY 2000

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference /.		FOR FURTHER ACTION	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)
International application No PCT/DK99/00549	International filing date (day/month/year) 12/10/1999	Priority date (day/month/year) 12/10/1998	
International Patent Classification (IPC) or national classification and IPC B29C67/00			
Applicant DICON A/S et al.			

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.



2. This REPORT consists of a total of 7 sheets, including this cover sheet.

- ☐ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☒ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☒ Certain observations on the international application

Date of submission of the demand 12/04/2000	Date of completion of this report 24 05 2000
Name and mailing address of the international preliminary examining authority  European Patent Office D-80298 Munich Tel +49 89 2399 - 0 Tx 523656 epmu d Fax +49 89 2399 - 4465	Authorized officer Deubler, U Telephone No +49 89 2399 2923 

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/DK99/00549

I. Basis of the report

1. This report has been drawn on the basis of (*substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments*):

Description, pages:

1-17 as originally filed

Claims, No.:

1-17 as originally filed

Drawings, sheets:

1/2.2/2 as originally filed

2. The amendments have resulted in the cancellation of:

- ☐ the description. pages:
☐ the claims. Nos.:
☐ the drawings. sheets:

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

4. Additional observations, if necessary:

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/DK99/00549

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes: Claims 1 - 17
	No: Claims
Inventive step (IS)	Yes: Claims 1 - 17
	No: Claims
Industrial applicability (IA)	Yes: Claims 1 - 17
	No: Claims

2. Citations and explanations

see separate sheet

VI. Certain documents cited

1. Certain published documents (Rule 70.10)

and / or

2. Non-written disclosures (Rule 70.9)

see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

see separate sheet

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/DK99/00549

The following documents (D) are referred to in this report :

- D1: WO 98 47042 A1 (DICON A/S) 22 October 1998
- D2: WO 98 47048 A1 (DICON A/S) 22 October 1998
- D3: US 4 575 330 A (CHARLES W. HULL) 11 March 1986
- D4: EP-A-0 676 275

As to V. :

- 1.) The invention relates to a rapid prototyping apparatus for the manufacturing of three-dimensional objects by additive treatment of cross sections comprising a wholly or partially light-sensitive material, said apparatus comprising at least one light source for illumination of a cross-section of the light-sensitive material by at least one spatial light modulator of individually controllable light modulators.

The invention further relates to a method of manufacturing three-dimensional objects by means of a rapid prototyping apparatus where a wholly or partially light-sensitive material is treated by at least one light source illuminating of a cross-section of the material by at least two modulator arrangements of individually controllable light modulators.

An apparatus and a method of this type are known (see e.g. EP-A-0 676 275).

The object of the invention is to provide an apparatus and a method for manufacturing large-scale three-dimensional objects in a reasonable time.

This object is achieved by optically coupling at least one light source to a plurality of light guides arranged with respect to the spatial light modulator arrangement in such a manner that each light guide illuminates a sub-area of the cross-section

None of the documents cited in the INTERNATIONAL SEARCH REPORT and **published prior to the earliest priority date** of the present application discloses or renders obvious the combination of these features in their entirety.

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/DK99/00549

Therefore independent claims 1 and 15 meet the requirements of Article 33 (2) and (3) PCT.

- 2.) The dependent claims 2 to 14, 16 and 17 are related to further particular embodiments.

Therefore claims 2 to 14, 16 and 17 meet the requirements of Article 33 (2) and (3) PCT either.

As to VI. :

Applicant's attention is drawn to documents D1 and D2. These documents have earlier priority dates and might be relevant as to novelty (Article 33(2) PCT) when the applicant continues with the application in a regional phase.

As to VII. :

- 1.) The features of the claims are **not all** provided with reference signs placed in parentheses contrary to Rule 6.2(b) PCT.
- 2.) Contrary to the requirements of Rule 5.1(a)(ii) PCT, the relevant background art disclosed in the documents D1 and D2 is not mentioned in the description, nor are these documents identified therein.
- 3.) The object of the invention (single inventive concept !) should have clearly been indicated in the description (e.g. "It is **the object** of the invention to improve ... etc.") and this single object should have completely be met by the invention as

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/DK99/00549

defined in the independent claim(s).

On page 4, lines 4 to 8 of the description it is stated that one of the purposes of the invention is to create a design system that may be applied in relation to the design of various types of RPA systems without requiring significant design modifications. However from the independent claims 1 and 15 it is not clear how this last object is attained.

- 4.) It should also have been indicated in the description on which prior art document the preamble of the independent claims is based.

As to VIII. :

The following items in the claims are not clear (Article 6 PCT) :

Claim 1 : What is meant by "additive treatment" ?

Which cross-section is meant by "cross-section" ?

What is specifically meant by "spatial light modulator" ?

What is specifically meant by "light guide" ?

Additionally, the matter for which protection is sought is not clearly defined.

The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged ... in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 3 : The reference sign 8 is used twice for two different features, rendering sign 8 unclear.

Claim 4 : The matter for which protection is sought is not clearly defined. The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged ... in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 6 : Although claim 6 depends on claims 1 to 5 it is not clear for what protection

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/DK99/00549

is sought, as claim 6 relates to an "illumination" whereas claims 1 to 5 refer to a rapid prototyping apparatus (see also para IV. above).

Additionally, the question of unity of invention (Rule 13.1 PCT) is not clear. Claims 1 to 5 and 7 to 17 are related to a rapid prototyping apparatus and to a method of manufacturing three-dimensional objects by means of a rapid prototyping apparatus, whereas claim 6 is related to an illumination device. It cannot be seen how these two different subject-matters (see first invention : "apparatus and method for rapid prototyping" and see second invention : "illumination device") are so linked as to form a single general inventive concept.

Therefore, also the requirements of Rule 13.1 PCT are not met.

Claim 7 : What is meant by "transverse" ? ("transverse" relative to what ?)

Claim 8 : The matter for which protection is sought is not clearly defined. The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 9 : What is meant by "surface profiles of the spatial modulator" ?

It is not clear which control parameters are controlled by the control circuit.

Claim 11: What is meant by "illumination device" in view of "exposure head" (see claim 10) ?

Claim 14: The matter for which protection is sought is not clearly defined. The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged ... in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 15: Although this claim relates to a method, its characterizing part contains only apparatus features but not a single method feature.

Therefore the category of this claim is not clear.

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference	FOR FURTHER ACTION	see Notification of Transmittal of International Search Report (Form PCT ISA 220) as well as, where applicable, item 5 below.
International application No. PCT/DK 99/00549	International filing date (day month year) 12 October 1999	(Earliest) Priority Date (day month year) 12 October 1998
Applicant Dicon A/S et al		

This international search report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This international search report consists of a total of 2 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. ☐ Certain claims were found unsearchable (See Box I).
2. ☐ Unity of invention is lacking (See Box II).
3. ☐ The international application contains disclosure of a nucleotide and/or amino acid sequence listing and the international search was carried out on the basis of the sequence listing
 - ☐ filed with the international application.
 - ☐ furnished by the applicant separately from the international application,
 - ☐ but not accompanied by a statement to the effect that it did not include matter going beyond the disclosure in the international application as filed.
 - ☐ transcribed by this Authority.
4. With regard to the title, ☒ the text is approved as submitted by the applicant.
☐ the text has been established by this Authority to read as follows:
5. With regard to the abstract,
 - ☒ the text is approved as submitted by the applicant.
 - ☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.
6. The figure of the drawings to be published with the abstract is:
Figure No. 1
 - ☐ as suggested by the applicant.
 - ☐ because the applicant failed to suggest a figure.
 - ☒ because this figure better characterizes the invention.☐ None of the figures.

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B29C 67/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B29C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9847042 A1 (DICON A/S), 22 October 1998 (22.10.98), page 11, line 9 - line 35, figure 1, claims 1-22, abstract --	1-17
X	WO 9847048 A1 (DICON A/S), 22 October 1998 (22.10.98), figures 3,4, claims 1-21, abstract --	1-17
A	US 4575330 A (CHARLES W. HULL), 11 March 1986 (11.03.86), abstract -- -----	1-17

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

& document member of the same patent family

Date of the actual completion of the international search

2 February 2000

Date of mailing of the international search report

21 03 2000

Name and mailing address of the International Searching Authority
European Patent Office P.B. 5818 Patentlaan 2
NL-2280 HV Rijswijk
Tel(+31-70)340-2040 Tx 31 651 epo nl
Fax(+31-70)340-3016

Authorized officer

Ulrika Nilsson/MP
Telephone No.

INTERNATIONAL SEARCH REPORT
Information on patent family members

S 52171

02/12/99

International application No.

PCT/DK 99/00549

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
WO	9847042	A1	22/10/98	AU	6919198 A	11/11/98	
				AU	6919298 A	11/11/98	
				WO	9847048 A	22/10/98	

WO	9847048	A1	22/10/98	AU	6919198 A	11/11/98	
				AU	6919298 A	11/11/98	
				WO	9847042 A	22/10/98	


US	4575330	A	11/03/86	AT	97506 T	15/12/93	
				AT	165270 T	15/05/98	
				DE	535720 T	27/06/96	
				DE	3587656 D,T	28/04/94	
				DE	3588184 D,T	17/09/98	
				EP	0171069 A,B	12/02/86	
				EP	0535720 A,B	07/04/93	
				EP	0820855 A	28/01/98	
				HK	1001701 A	00/00/00	
				HK	1006347 A	00/00/00	
				JP	1827066 C	28/02/94	
				JP	2048422 B	25/10/90	
				JP	62035966 A	16/02/87	
				SG	48918 A	18/05/98	
				US	4929402 A	29/05/90	
				US	5174943 A	29/12/92	
				US	5236637 A	17/08/93	
				US	5344298 A	06/09/94	
				US	5554336 A	10/09/96	
				US	5556590 A	17/09/96	
				US	5569431 A	29/10/96	
				US	5571471 A	05/11/96	
				US	5573722 A	12/11/96	
				US	5630981 A	20/05/97	
				US	5779967 A	14/07/98	
				US	5785918 A	28/07/98	
				US	5814265 A	29/09/98	

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference <i>J.</i>	FOR FURTHER ACTION		See Notification of Transmittal of International Preliminary Examination Report (Form PCT/PEA/416)
International application No. PCT/DK99/00549	International filing date (day/month/year) 12/10/1999	Priority date (day/month/year) 12/10/1998	
International Patent Classification (IPC) or national classification and IPC A29C67/00			
Applicant DICON A/S et al.			
<p>1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of 7 sheets, including this cover sheet.</p> <p><input type="checkbox"/> This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).</p> <p>These annexes consist of a total of sheets</p>			
<p>3. This report contains indications relating to the following items:</p> <ul style="list-style-type: none"> I <input checked="" type="checkbox"/> Basis of the report II <input type="checkbox"/> Priority III <input type="checkbox"/> Non-establishment of opinion with regard to novelty, inventive step and industrial applicability IV <input type="checkbox"/> Lack of unity of invention V <input checked="" type="checkbox"/> Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement VI <input checked="" type="checkbox"/> Certain documents cited VII <input checked="" type="checkbox"/> Certain defects in the international application VIII <input checked="" type="checkbox"/> Certain observations on the international application 			
Date of submission of the demand 12/04/2000		Date of completion of this report 24.05.2000	
Name and mailing address of the international preliminary examining authority  European Patent Office D-80299 Munich Tel: +49 89 2399-1 Fax: 523666 comu d Telex: 449 89 2399 - 4465		Authorized officer Daubier U Telephone No. +49 89 2399 2923	



**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/DK99/00549

I. Basis of the report

1. This report has been drawn on the basis of (*substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.*):

Description, pages:

1-17 as originally filed

Claims, No.:

1-17 as originally filed

Drawings, sheets:

1/2, 2/2 as originally filed

2. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
☐ the claims, Nos.:
☐ the drawings, sheets:

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

4. Additional observations, if necessary:

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/DK99/00549

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability: citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes:	Claims	1 - 17
	No:	Claims	
Inventive step (IS)	Yes:	Claims	1 - 17
	No:	Claims	
Industrial applicability (IA)	Yes:	Claims	1 - 17
	No:	Claims	

2. Citations and explanations

see separate sheet

VI. Certain documents cited

1. Certain published documents (Rule 70.10)

and / or

2. Non-written disclosures (Rule 70.9)

see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

see separate sheet

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/DK99/00549

The following documents (D) are referred to in this report :

- D1: WO 98 47042 A1 (DICON A/S) 22 October 1998
- D2: WO 98 47048 A1 (DICON A/S) 22 October 1998
- D3: US 4 575 330 A (CHARLES W. HULL) 11 March 1986
- D4: EP-A-0 676 275

As to V. :

- 1.) The invention relates to a rapid prototyping apparatus for the manufacturing of three-dimensional objects by additive treatment of cross sections comprising a wholly or partially light-sensitive material, said apparatus comprising at least one light source for illumination of a cross-section of the light-sensitive material by at least one spatial light modulator of individually controllable light modulators.

The invention further relates to a method of manufacturing three-dimensional objects by means of a rapid prototyping apparatus where a wholly or partially light-sensitive material is treated by at least one light source illuminating of a cross-section of the material by at least two modulator arrangements of individually controllable light modulators

An apparatus and a method of this type are known (see e.g. EP-A-0 676 275).

The object of the invention is to provide an apparatus and a method for manufacturing large-scale three-dimensional objects in a reasonable time.

This object is achieved by optically coupling at least one light source to a plurality of light guides arranged with respect to the spatial light modulator arrangement in such a manner that each light guide illuminates a sub-area of the cross-section

None of the documents cited in the INTERNATIONAL SEARCH REPORT and **published prior to the earliest priority date** of the present application discloses or renders obvious the combination of these features in their entirety

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/DK99/00549

Therefore independent claims 1 and 15 meet the requirements of Article 33 (2) and (3) PCT.

- 2.) The dependent claims 2 to 14, 16 and 17 are related to further particular embodiments.

Therefore claims 2 to 14, 16 and 17 meet the requirements of Article 33 (2) and (3) PCT either.

As to VI. :

Applicant's attentions is drawn to documents D1 and D2. These documents have earlier priority dates and might be relevant as to novelty (Article 33(2) PCT) when the applicant continues with the application in a regional phase.

As to VII. :

- 1.) The features of the claims are **not all** provided with reference signs placed in parentheses contrary to Rule 6.2(b) PCT.
- 2.) Contrary to the requirements of Rule 5.1(a)(ii) PCT, the relevant background art disclosed in the documents D1 and D2 is not mentioned in the description, nor are these documents identified therein.
- 3.) The object of the invention (single inventive concept ') should have clearly been indicated in the description (e.g. "It is **the object** of the invention to improve ... etc.") and this single object should have completely be met by the invention as

defined in the Independent claim(s).

On page 4, lines 4 to 8 of the description it is stated that one of the purposes of the invention is to create a design system that may be applied in relation to the design of various types of RPA systems without requiring significant design modifications. However from the independent claims 1 and 15 it is not clear how this last object is attained

- 4) It should also have been indicated in the description on which prior art document the preamble of the independent claims is based.

As to VIII. :

The following items in the claims are not clear (Article 6 PCT) :

Claim 1 : What is meant by "additive treatment" ?

Which cross-section is meant by "cross-section" ?

What is specifically meant by "spatial light modulator" ?

What is specifically meant by "light guide" ?

Additionally, the matter for which protection is sought is not clearly defined. The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged ... in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 3 : The reference sign 8 is used twice for two different features, rendering sign 8 unclear.

Claim 4 : The matter for which protection is sought is not clearly defined. The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged ... in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 6 : Although claim 6 depends on claims 1 to 5 it is not clear for what protection

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/DK99/00549

is sought, as claim 6 relates to an "illumination" whereas claims 1 to 5 refer to a rapid prototyping apparatus (see also para IV. above).

Additionally, the question of unity of invention (Rule 13.1 PCT) is not clear. Claims 1 to 5 and 7 to 17 are related to a rapid prototyping apparatus and to a method of manufacturing three-dimensional objects by means of a rapid prototyping apparatus, whereas claim 6 is related to an illumination device.

It cannot be seen how these two different subject-matters (see first invention : "apparatus and method for rapid prototyping" and see second invention : "illumination device") are so linked as to form a single general inventive concept.

Therefore, also the requirements of Rule 13.1 PCT are not met.

Claim 7 : What is meant by "transverse" ? ("transverse" relative to what ?)

Claim 8 : The matter for which protection is sought is not clearly defined. The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 9 : What is meant by "surface profiles of the spatial modulator" ?

It is not clear which control parameters are controlled by the control circuit.

Claim 11: What is meant by "illumination device" in view of "exposure head" (see claim 10) ?

Claim 14: The matter for which protection is sought is not clearly defined. The claim attempts to define the subject-matter in terms of the result to be achieved (see "arranged ... in such a manner that ...") which merely amounts to a statement of the underlying problem. The technical features necessary for achieving this result should have been added.

Claim 15: Although this claim relates to a method, its characterizing part contains only apparatus features but not a single method feature.

Therefore the category of this claim is not clear.


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B29C 67/00		A1	(11) International Publication Number: WO 00/21735
			(43) International Publication Date: 20 April 2000 (20.04.00)
(21) International Application Number: PCT/DK99/00549 (22) International Filing Date: 12 October 1999 (12.10.99) (30) Priority Data: PA 1998 01298 12 October 1998 (12.10.98) DK (71) Applicant (for all designated States except US): DICON A/S [DK/DK]; Sønderskovvej 5, DK-8520 Lystrup (DK). (72) Inventor; and (75) Inventor/Applicant (for US only): HENNINGSEN, Henning [DK/DK]; Nørregade 25, DK-8670 Låsby (DK). (74) Agent: PATENTGRUPPEN APS; Arosgaarden, Aaboulevar- den 31, DK-8000 Aarhus C (DK).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: RAPID PROTOTYPING APPARATUS AND METHOD OF RAPID PROTOTYPING

(57) Abstract

The invention relates to a rapid prototyping apparatus for the manufacturing of three dimensional objects by additive treatment of cross sections comprising a wholly or partially light-sensitive material (2), said apparatus comprising at least one light source for illumination of a cross section of the light-sensitive material (2) by at least one spatial light modulator of individually controllable light modulators, wherein at least one light source is optically coupled with a plurality of light guides (8) arranged with respect to the spatial light modulator arrangement in such a manner that each light guide (8) illuminates a sub-area of the cross section. According to the invention, it is possible to obtain a significant simplification of an RP design system, just as the apparatus designed are essentially capable of creating prototypes of any size, according to the invention.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

RAPID PROTOTYPING APPARATUS AND METHOD OF RAPID PROTOTYPING

Background of the technique

5 The invention relates to a so-called rapid prototyping apparatus for the manufacturing of three dimensional objects by additive treatment of cross sections, said cross sections consisting of a wholly or partially light-sensitive material, said rapid prototyping apparatus comprising at least one light source as stated in the preamble of claim 1.

10

The invention also relates to a method of manufacturing of three dimensional objects by means of a rapid prototyping apparatus wherein a wholly or partially light-sensitive material is treated by means of illumination of a cross section of the material by at least one spatial light modulator arrangement of controllable light modulators as stated in the preamble of claim 15.

15

Background of the invention

In connection with the manufacturing of mechanical prototypes, and especially during the production design processes, recent years have introduced various types of rapid prototyping techniques (RP) where three dimensional objects are manufactured by sequential cross section layers generated by a given illumination, sintering, setting or placing of material etc. on each cross section. The individual cross sections are e.g. generated as computer-aided designs. The advantage of RP is that the manufacturing of expensive molding tools for the design of the apparatus becomes superfluous for its manufacturing, just as difficult and time-consuming modifications of a molding tool may almost be completely avoided.

20

25

Also, various techniques have been made available for the manufacturing of relatively inexpensive and fast prototype or 0 series molding tools based on a manufactured Rapid Prototype.

30

One type of RP technique is used in e.g. stereolithographic apparatuses, also called SLAs. This technique is based on the individual layers or cross sections of a prototype being manufactured by a photo-sensitive medium and hardened into one monolithic prototype by means of computer-aided illumination.

5

Apparatuses and techniques of the above-mentioned type are described in e.g. US patent No. 4,575,330 where the illumination determined by the cross section is described as a laser drawing of each cross section or a transilluminating mask exposing the desired cross section.

10

Meanwhile, one of the disadvantages of the above-mentioned system is that the distribution of light over the cross section limits the design flexibility of the system as adjustments of existing sources of illumination are limited to certain system dimensions.

15

Thus, when manufacturing large-scale models, it is necessary to divide a given desired prototype into several prototype parts, manufacture these parts individually by separate runs and then finally complete the prototype by joining the parts by e.g. pasting.

20

However, this process involves a significant risk of running into technical problems and complications. It is necessary to take into account e.g. marginal problems for each prototype part as the tolerance level between adjacent prototype parts differs from the tolerance levels existing between each of the manufactured layers comprising the individual prototype parts. Meanwhile, this may be prevented by taking the proper precautions in relation to the illumination algorithms or by an actual mechanical manufacturing of the individual prototype parts if necessary. This compensation strategy would be particularly difficult on the "vertical level" and may e.g. lead to both under- and overillumination and consequently to tolerance or joining errors between the individual layers.

30

Problems could also arise in connection with the pasting of the prototype parts as the hardening of the paste may cause contractions or expansions in places where the paste is used. These changes in the hardening would often be of a non-linear character and thereby difficult to estimate or predict beforehand.

5

Another problem is that these joinings generally cause problems of strength when used on large-scale models.

10 An additional and significant problem is that common RPA materials (materials for Rapid Prototyping Apparatuses) such as acrylates and epoxy are quite hazardous making manual runs undesirable. In this connection, it should be mentioned that the joining of the individual prototypes must be carried out manually which adds to the costs and makes working conditions difficult. Also, due to the manual work to be carried out as described in accordance with the method above, the encapsulation of
15 the apparatus makes it more difficult for the creators to carry out their work. This problem is even more outspoken in relation to the use of e.g. hazardous or directly toxic materials.

20 Finally, it should also be mentioned that the known method is quite time-consuming involving many hours and sometimes several days, depending on the size of the prototype.

EP 0 676 275 discloses a DMD-based stereolithographic device comprising a plurality of illumination modules, each module comprising a dedicated light source.
25 By varying the number of the utilized modules, an arbitrary size and form of the illumination head may be obtained. However, the device has the disadvantage of being voluminous and quite expensive. Moreover, the mutual variation of the light sources results in a different degree of illumination of the various illuminated sub-areas, and consequently in both underexposure and overexposure of as well the
30 vertical as horizontal plane of the illuminated surface.

The purpose of the invention is to create an RP technique and an RP apparatus that
5 may be used for the manufacturing of e.g. large-scale prototypes while it is also the
purpose of the invention to create a design system that may be applied in relation to
the design of various types of RPA systems without requiring significant design
modifications.

10 **The invention**

The invention relates to a rapid prototyping apparatus for the manufacturing of three
dimensional objects by additive treatment of cross sections comprising a wholly or
partially light-sensitive material, said apparatus comprising at least one light source
for illumination of a cross section of the light-sensitive material by at least one
15 spatial light modulator of individually controllable light modulators, wherein at least
one light source being optically coupled with a plurality of light guides arranged with
respect to the spatial light modulator arrangement in such a manner that each light
guide illuminates a sub-area of the cross section.

20 The invention provides the opportunity to design a given RP system for handling
prototypes of any size as the number of light emitters and thereby individual areas to
be covered may be increased or decreased until it matches the size of the prototype in
question. In this manner, it becomes possible and simple to design an illumination
system for an RP system constructed as a module system having a number of
25 illumination modules that may be suitably added or arranged in relation to the system
design. This flexibility may in principle be utilized for both the design of RPs for
large-scale prototypes and of more consumer-oriented RPs for small-scale models.

Also, the multiple light emitters provide the opportunity to use light sources in the
30 shape of dots. By applying a system in accordance with the invention, it is possible to
obtain a diameter of the punctual point of illumination of as little as 10μ in
comparison with the existing technique with an absolute low of 80μ . This is of great

advantage when manufacturing prototypes where great precision properties are required. This includes e.g. the manufacturing of tools where the prototype is provided with a metal coat subsequent to the manufacturing prior to being used for the molding of a tool.

5

Certain areas of this technique apply a prolonged light source such as e.g. a fluorescent lamp or an excimer lamp in order to be able to produce prototypes of a certain dimension. However, according to the optical laws, prolonged light sources alone only provide the opportunity to create a prolonged point of illumination which, in turn, significantly limits the potential of making details in the prototype. Apart from that, prolonged light sources are subject to relatively large losses.

10

According to the invention, the definition of light is broad and includes electromagnetic radiation, both within and outside the visible spectrum.

15

Alternatively, quite a lot of optics must be used in connection with the prolonged light sources in order to adjust the shape of the point of illumination. Naturally, this makes the system more expensive while also requiring a great degree of accuracy when monitoring the optics.

20

The multiple light emitters also provide the opportunity to increase the illumination effect over the illuminated cross section since each area can be illuminated by an individual light emitter or even an illuminant. This is an advantage as it becomes possible to tailor the illumination effect to the individual prototype in such a manner that it is created with optimal illumination effect.

25

By, as specified in claim 1, illuminating the sub-areas it is possible to obtain an effective sum of the number of sub-areas.

30

A particular advantage of an illumination system according to the invention is also that the illumination of the sub-areas provides the opportunity to design sub-areas in

separate illumination modules that may easily be replaced as the individual illumination modules may be mutually aligned.

5 This should be seen in the light of the fact that the illumination modules must be regarded as being fairly vulnerable in relation to various RP technologies, as the illumination system will be damaged permanently once it has been put in contact with certain kinds of media which is why the possibility to create a fairly easy method of replacement of the illumination shutters is desirable.

10

Also, several of the existing illumination technologies have a limited useful life. This includes the LCD-based light valves where the strong luminous excitation, especially with UV-light, results in a risk of a gradual breakdown of the active crystals, which is also the case with the micromechanical shutter, according to an embodiment of
15 this invention, said micro mechanical shutters being expected to have a limited number of on/off shifts.

Treatment is defined in its broadest sense and includes e.g. hardening or decomposition of the light-sensitive material.

20

By, as specified in claim 2, letting each spatial modulator arrangement comprise transmissive light valves, it is possible to obtain an additional advantageous embodiment, according to the invention. By using light guides, the above-mentioned advantage of easy replacement of the illumination modules will be distinct as the
25 mutual alignment of the illumination modules only requires a supplementary uncritical assembly or disassembly of the light-emitting end of a light source. Thus, no critical calibration of the illumination system is needed.

By distributing the light through several light guides, each illuminating a number of
30 light valves, it is also possible to use more light sources in a simple manner as each light source may be dedicated to one particular light guide so that the effect is maximized.

Another advantage of distributing light by means of light guide is that the light may be suitably mixed in optical couplers or similar devices in order to obtain a greater total transmitted effect in the individual light guide.

5

Yet another advantage of the invention is that it gradually becomes possible to obtain increased power inputs from e.g. lamps in the UV-area resulting in the effect transmitted to the light valves being so great that the individual light guides may emit a light that has sufficient energy to illuminate more light valves simultaneously.

10

In connection with the use of e.g. UV lamps, it has also turned out that the introduction of "macro illumination areas", i.e. areas illuminated by one single optical fiber per area, does not result in any significant edge effects between each illumination area, just as it has turned out that potential and significant variations between the emitted effects from each light guide (resulting from a varying intensity profile of a connected lamp e.g. due to various placings of the coupling optics and the individual fibers in relation to the lamp) may be compensated for by a suitable mix of the light guides whereby the result of the illumination is a homogenous visual impression without any significant differences in intensity in the edge areas.

20

The above-mentioned mix may e.g. be carried out in relation to the adjacent macro illumination areas that may be provided with an optical effect which does not vary significantly while macro illumination areas situated relatively far from each other may vary in intensity without resulting in significant visual interruptions on the illumination surface.

25

An additional advantage, according to the invention, is that it is possible to filtrate light emitted to or from the individual optical fibers so that the illumination intensity is homogenous for all or a part of the optical fibers.

30

According to the invention, an apparatus like this may be based on a relatively simple technique compared to the existing techniques while also creating a high

solution, high illumination speed, good precision properties and a uniform illumination intensity over a very large illumination area.

5 The invention is particularly advantageous in relation to light valves associated with a relatively great loss. An example of such light valves may e.g. be spatial light modulators such as LCD, PDLC, PLZT, FELCD and Kerr cells. Other types of light valves may e.g. be electromechanical reflection-based light valves of the DMD type.

10 Thus, according to the invention, it is possible to sum up light in a simple manner over a large surface with the use of relatively few light guides, just as it is possible to orient the light emitters of the illumination system relatively freely as the light emitters consist of light guiding ends and not an optical system, drivers and cooling means.

15 A particularly advantageous embodiment of the invention is obtained with transmissive light valves since they generate few optical losses which may be imperative for the functionality of certain applications.

20 By, as specified in claim 3, letting the apparatus comprise a first lens arrangement, said first lens arrangement comprising at least one microlens arranged with respect to each light valve in such a manner that that the emitted light by the light guide(s) (8) focuses on or in proximity of the optical axis of the individual light valves, it is possible to obtain a high degree of utilization of the light effect and rapid transit times generated by the light source.

25

By, as specified in claim 4, letting the rapid prototyping apparatus comprise a second micro lens arrangement between the light valves and the illumination surface in such a manner that light transmitted through the light channels of the individual light valves is suitably focused on the illumination surface, it is possible to transmit the
30 light from each channel in smaller dots with high intensity on the illumination surface.

The invention also provides a very advantageous possibility of preventing operating errors. Thus, it becomes possible to move the illumination surface as far away as possible from the light valve arrangement which reduces the risk of the media in question coming into contact with the light valve arrangement.

5

The illumination distance may be determined by the design of the micro lenses.

This property is particularly advantageous as this technique - as opposed to other applications - is technically vulnerable to position inaccuracies in the z surface.

10

By, as specified in claim 5, letting the light guides consist of preferably multi mode fibers, it is possible to obtain a limited loss of illumination intensity and great flexibility in the design by the spacious placing of the individual elements.

15 By using multi mode fibers it also becomes possible to illuminate the illumination surface with a wide spectrum of light.

By, as specified in claim 6, letting at least one on the light sources consist of a short arc gap lamp, a high emitted light effect from an area of a limited physical scope is
20 obtained (high radiation power).

By, as specified in claim 7, letting the the individual light valves be arranged in rows in the transverse direction of the surface at a given mutual distance, said rows being mutually displaced in the transverse direction, it becomes possible to divide the light
25 linearly and broadly.

By, as specified in claim 8, arranging the rows in such a manner that the projection on the transverse direction of the surface provided by the light valves results in a number of illumination points at a given mutual distance in the transverse direction,
30 it becomes possible to emit light in dots with a significantly improved solution than would have been the case if it had been determined by the physical extent of the valves and if placed in one single transverse directional row.

By, as specified in claim 9, letting the surface profile(s) of the spatial modulator arrangements be arranged on one or more exposure heads, said exposure heads and said illumination surface being designed to make a relative movement, said rapid
5 prototyping apparatus being provided with a control circuitry for control of the spatial light modulator arrangements in dependency of the movement between the exposure head and the illumination surface, an advantageous embodiment is obtained, according to the invention.

10 By, as specified in claim 10, letting the exposure head(s) comprise a bar whose movement over the illumination surface consists of one single progressing movement in the transverse direction of the bar, it is possible to create illuminated dots covering the entire or a significant part of the illumination surface due to the scanning
movement.

15 By, as specified in claim 11, letting the illumination device between the spatial light modulator arrangement and the illumination surface comprise additional optical means for the spreading of light beams provided by spatial light modulator arrangement over the illumination surface, it becomes possible to expose an area
20 which is physically larger than the area covered by the light channels whereby non-active edge areas around a light valve arrangement may also be illuminated.

By, as specified in claim 12, letting the spatial light modulator arrangement of the illumination unit be made of spatial light valves such as LCD, PDLC, PLZT, FELCD
25 or Kerr cells, great design flexibility is obtained in relation to the light modulator principle of the individual applications which makes the manufacturing of standardized components cheaper.

By, as specified in claim 13, letting the spatial light modulator arrangement of the
30 illumination device consist of reflective electromechanical light valves such as DMD, it is possible to obtain another advantageous embodiment of the invention which is based on commercially wide-spread technologies.

By letting the light valves of the illumination unit consist of transmission-based electromechanical light valves, a solution is obtained with only a small reduction of light through the modulator. This is particular advantageous in relation to even small improvements of the available radiation intensity which results in a significantly reduced duration of illumination. This must be seen in the light of the fact that an RP prototype is made up by several layers of material and the total time to be gained is therefore significant.

- 10 By, as specified in claim 14, letting the light guides of the illumination unit be arranged with respect to the spatial light modulator arrangement in such a manner that the furnished optical energy for each subset of light modulators does not vary significantly once the subsets of light modulators illuminate adjacent sub-areas in close proximity to each other on the illumination surface, the allowed variation in
15 light intensity between all light sources is obtained and may be increased without being visible.

The invention also relates to a method, as specified in claim 15, of the manufacturing of three dimensional objects by means of a rapid prototyping apparatus where at least
20 one light source is optically coupled with a plurality of light guides arranged with respect to the spatial light modulator arrangement in such a manner that each light guide illuminates a sub-area of the cross section.

In this manner, it is possible to obtain an illumination system capable of producing
25 prototypes at a speed which is currently up to 10 time faster than the existing techniques and methods.

The bigger the model, the bigger the advantage according to the invention.

- 30 By, as specified in claim 16, letting the wholly or partially light-sensitive material be placed as a layer on a plate in a container and subsequently expose it to the RP device before placing a new layer on top of the previous layer, a gradual build-up of

the desired prototype is obtained. According to the invention, the method allows for the construction of one layer and joining it with a previous layer in one single work process.

- 5 By, as specified in claim 17, letting the RP device comprise a computer-aided design program capable of converting the 3D representation of the prototype to be constructed into files containing a cross section of the prototype, the contents of said files being used to control the controllable light modulators, it is possible to convert e.g. graphic representations into a given prototype. This process takes place at a very
10 slow conversion speed, according to the invention.

Figures

The invention will be described in detail in the following with reference to the figures where

15

- Fig. 1 shows an example of an SLA application according to the invention and
Fig. 2 shows an additional example of the SLA application according to the invention.

20 Detailed description

Figure 1 shows a schematic diagram of an embodiment according to the invention.

- Microshutters or light valves are defined in the broadest sense as transmissive light blinders that may e.g. be made of micromechanical shutters. The individual shutter
25 elements may e.g. be of the type described in the French patent application No. 9412928 or the type described in the corresponding EP-A 709 706 as the preferred embodiment of the invention deems it decisive that the light to be modulated is transmitted directly through the individual microshutters in order to create a minimal loss of transmission.

30

The shown Rapid Prototyping (RP) apparatus comprises a stationary part whose most significant component consists of a container 1 designed to contain a suitable amount

of liquid RP material 2. An RP material is the material of which the RP prototype will be made such as epoxy, acrylates or other RP materials. In addition, the stationary part is designed with a leader 4 which can be positioned for various purposes between the stationary part and a movable illumination device 3. The illumination device may also comprise corresponding leader (not shown) for e.g. a vertical movement. The RP apparatus also comprises other computer-controlled means (not shown) designed to control a relative movement of the illumination device 3 corresponding to a suitable computer-aided design of the illumination system of the RP apparatus.

The illumination device 3 is also provided with an illumination system whose most important components will be described in the following.

The illumination device 3 comprises a light source arrangement 6 mounted on a rack 5 comprising known necessary means of illumination together with a power supply and cooling means. The light source is illustrated as a UV source in the shown example. The light source with its aggregates and cooling means may be stationary or movable.

The light source arrangement 6 is optically connected with bundles 7 of optical multi mode fibers. These bundles 7 spread into eight individual fibers 8 where each fiber illuminates a microshutter arrangement of e.g. 588 micromechanical light valves. Thus, in unison, the eight individual fibers illuminate an illumination device 9 comprising eight microshutter arrangements, each constituting an individual area of the entire microshutter arrangement.

The construction itself and the orientation of these light valves have been described in the international application Nos. PCT/DK98/00154 and PCT/DK98/00155 also by the inventor of this invention and are hereby incorporated by reference.

Each individual area comprises a number of light valves that may be individually controlled electrically by a connected control circuitry (not shown). The light valve

arrangement may e.g. be an LCD display with a given desired solution. However, micromechanical shutters are preferable.

5 The entire area of light valves is illuminated by one single light guide 8 arranged in such a manner that a light beam emitted from the light guide 8 may furnish all light valves occupying an individual area with optical energy.

It should be noted that the light beam will usually be furnished through the collimating optics to the sub-areas in such a manner that the light beam with which
10 the spatial light modulator has been furnished is uniform in respect of energy over the modulator area.

The microshutters in the illumination modules 9 have been designed to conduct a scanning over a scanning line of 25 to 30 centimeters in the shown illumination
15 arrangement.

It is obvious from the example that the length of the scanning line to be used, i.e. one of the maximum dimensions of a manufactured RP prototype, may be shaped as desired in contrast to existing techniques since the "local" illumination of the
20 individual illumination modules may be oriented in any direction on the illumination surface. Apart from that, it is also immediately obvious that the method of illumination by means of one central light source and the coupled optical guides provides a tremendous advantage in respect of design which is naturally reflected financially and in the quality of the completed construction. The shown construction
25 is thus extremely robust and any defects or damaged light modulators may easily be replaced.

In addition, the apparatus is provided with a control circuitry (not shown) designed to provide a relative Z positioning (vertical movement) and orientation between the
30 illumination system and a material 2. An example of such materials has been described in detail in the example of an embodiment shown in figure 2.

Figure 2 shows an RP apparatus comprising a stationary part consisting of a rigidly mounted bar provided with a slide 27 moveable on the X and Y plane. Said slide is provided with a holder 28 for fixation of an illumination device, said illumination device being movable horizontally while the device is being fixed vertically.

5

The illumination device also comprises a light modulator 21 consisting of a number of light valves. The furnishing of light from a light source to the valves is provided for by mounting spots for light fibers 22, the light emitting ends of said light fibers being provided with a connector that makes it easy and simple to create a connection without an actual calibration requirement.

10

The stationary part of the RP apparatus also comprises an elevator 20 wherein a slide 29 is moving vertically. The slide is mechanically connected to a plate 24 whereby it is possible to move the plate vertically. The plate is submerged into a container 23 designed to contain an suitable amount of liquid RP material and may be contained below the surface.

15

The container 23 is placed under the illumination device which may be moved over the container horizontally by the slide arrangement 26 to 28 while illuminating the RP material in the suitable manner through the light valves of the illumination device. When illuminated, the exposed amount of RP material will harden from the surface and down to where the plate is submerged. Subsequent to the hardening, the plate is submerged into the liquid material once again and as the plate is provided with a number of perforation holes 23, the submersion may take place quickly while avoiding unnecessary stirring of the material.

20

25

Once the plate has been repositioned vertically, it is only submerged so much as to make it possible to create a new layer of liquid RP material on top of the previously hardened layers. An illumination of the new layer is then carried out.

30

This technique is described in e.g. US 4,575,330 and US 5,174,931, both of which are hereby incorporated by reference.

It is naturally implicit that the container may also be movable and the illumination module stationary in another embodiment or that both units may be movable since a relative movement must take place between the two units. However, in the first
5 embodiment with the movable container, the RP material will most likely be more viscous or solid in order to avoid baffling and the formation of waves.

List of numbers used in the drawings/figures:

1. Container
- 5 2. Liquid RP material
3. Illumination device
4. Leader
5. Rack
6. Light source arrangement
- 10 7. Bundles of optical fibers
8. Light guides
9. Illumination modules
20. Elevator
21. Illumination module
- 15 22. Mounting spots for light emitting ends
23. Container for RP material
24. Plate
25. Perforations in plate
26. Bar
- 20 27. Slide for illumination device
28. Holder for illumination device
29. Slide for plate

Patent Claims

1. Rapid prototyping apparatus for the manufacturing of three dimensional objects by additive treatment of cross sections comprising a wholly or partially light-sensitive material (2), said apparatus comprising at least one light source for illumination of a cross section of the light-sensitive material (2) by at least one spatial light modulator of individually controllable light modulators,

characterized by

at least one light source being optically coupled to a plurality of light guides (8) arranged with respect to the spatial light modulator arrangement in such a manner that each light guide (8) illuminates a sub-area of the cross section.
2. Rapid prototyping apparatus of claim 1 characterized by each spatial modulator arrangement comprising transmissive light valves.
3. Rapid prototyping apparatus of claim 1 or 2 characterized by said apparatus comprising a first lens arrangement, said first lens arrangement comprising at least one micro lens arranged with respect to each light valve in such a manner that that the emitted light by the light emitter(s) (8) focuses on or in proximity of the optical axis of the individual light valves.
4. Rapid prototyping apparatus of claims 1 to 3 characterized by said apparatus comprising a second lens arrangement, said second lens arrangement comprising at least one micro lens arranged between the light valves and the illumination surface in such a manner that light transmitted through the light channels of the individual light valves is suitably focused on the illumination surface.
5. Rapid prototyping apparatus of claims 1 to 4 characterized by optical fibers, preferably multi mode fibers, constituting the optical light guides (8).

6. Illumination device of claims 1 to 5 characterized by at least one of the light sources being made of a short arc gap lamp.
- 5 7. Rapid prototyping apparatus of claims 1 to 6 characterized by the individual light valves being arranged in rows in the transverse direction of the surface at a given mutual distance, said rows being mutually displaced in the transverse direction.
- 10 8. Rapid prototyping apparatus of claims 1 to 7 characterized by the rows being arranged in such a manner that the projection of each individual light valve in the transverse direction on the surface results in a number of illumination points at a given mutual distance in the transverse direction.
- 15 9. Rapid prototyping apparatus of claims 1 to 8 characterized by the surface profile(s) of the spatial modulator arrangements being arranged on one or more exposure heads, said exposure heads and said illumination surface being designed to make a relative movement, said rapid prototyping apparatus being provided with a control circuitry for control of the spatial light modulator
20 arrangements in dependency of the movement between the exposure head and the illumination surface.
10. Rapid prototype apparatus of claims 1 to 9 characterized by the exposure head(s) comprising a bar whose relative movement over the
25 illumination surface consists of one single progressing movement in the transverse direction of the bar.
11. Rapid prototyping apparatus of claims 1 to 10 characterized by the
30 illumination device between the spatial light modulator arrangement and the illumination surface comprising optical means for the spreading of the light beams emitted by the light modulator arrangement over the illumination surface.

12. Rapid prototyping apparatus according to claims 1 to 11 characterized by the modulator arrangement of the illumination device being spatial light modulators such as LCD, PDLC, PLZT, FELCD or Kerr cells.
- 5 13. Rapid prototyping apparatus of claims 1 to 12 characterized by the modulator arrangement of the illumination device being reflective electromechanical light valves such as DMD.
- 10 14. Rapid prototyping apparatus of claims 1 to 13 characterized by the light guides of the illumination device being arranged with respect to the modulator arrangement in such a manner that the furnished optical energy to each subset of light valves does not vary significantly once the subsets of light valves illuminate adjacent sub-areas in close proximity to each other on the
- 15 illumination surface.
15. Method of manufacturing three dimensional objects by means of a rapid prototyping apparatus where a wholly or partially light-sensitive material is treated by at least one light source illuminating a cross section of the material
- 20 by at least two modulator arrangements of individually controllable light modulators,
- characterized by
- 25 at least one light source being optically coupled with a plurality of light guides (8) arranged with respect to the spatial light modulator arrangement in such a manner that each light guide (8) illuminates a sub-area of the cross section.
16. Method of claim 15 characterized by a wholly or partially light-sensitive material (2) being placed in a layer on a plate (24) in a container and subsequently exposed to an RP apparatus prior to creating a new layer on top
- 30 of the previous layer.

17. Method of claim 15 or 16 characterized by an RP apparatus being provided with a computer-aided design program wherein a 3D representation of the desired prototype is converted into files containing a cross section of the prototype and wherein the contents of the files are used to control the spatial light modulator arrangement.

1/2




Fig.1

2/2




Fig.2

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B29C 67/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B29C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9847042 A1 (DICON A/S), 22 October 1998 (22.10.98), page 11, line 9 - line 35, figure 1, claims 1-22, abstract --	1-17
X	WO 9847048 A1 (DICON A/S), 22 October 1998 (22.10.98), figures 3,4, claims 1-21, abstract --	1-17
A	US 4575330 A (CHARLES W. HULL), 11 March 1986 (11.03.86), abstract -- -----	1-17

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 February 2000

Date of mailing of the international search report

21.03.2000

Name and mailing address of the International Searching Authority
European Patent Office P.B. 5818 Patentlaan 2
NL-2280 HV Rijswijk
Tel(+31-70)340-2040 Tx 31 651 epo nl
Fax(+31-70)340-3016

Authorized officer

Ulrika Nilsson/MP
Telephone No.

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/DK 99/00549

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9847042 A1	22/10/98	AU 6919198 A AU 6919298 A WO 9847048 A	11/11/98 11/11/98 22/10/98
WO 9847048 A1	22/10/98	AU 6919198 A AU 6919298 A WO 9847042 A	11/11/98 11/11/98 22/10/98
US 4575330 A	11/03/86	AT 97506 T AT 165270 T DE 535720 T DE 3587656 D,T DE 3588184 D,T EP 0171069 A,B EP 0535720 A,B EP 0820855 A HK 1001701 A HK 1006347 A JP 1827066 C JP 2048422 B JP 62035966 A SG 48918 A US 4929402 A US 5174943 A US 5236637 A US 5344298 A US 5554336 A US 5556590 A US 5569431 A US 5571471 A US 5573722 A US 5630981 A US 5779967 A US 5785918 A US 5814265 A	15/12/93 15/05/98 27/06/96 28/04/94 17/09/98 12/02/86 07/04/93 28/01/98 00/00/00 00/00/00 28/02/94 25/10/90 16/02/87 18/05/98 29/05/90 29/12/92 17/08/93 06/09/94 10/09/96 17/09/96 29/10/96 05/11/96 12/11/96 20/05/97 14/07/98 28/07/98 29/09/98